



Structural category				
Outward appearance code		LMF22		
Outward appearance illustration				
Overall dimensions				
Flush	Detection distance		2mm	
	DC 6~ 36 VDC	NPN	NO	LMF22-3002NA
			NC	LMF22-3002NB
			NO+NC	
	PNP	NO	LMF22-3002PA	
		NC	LMF22-3002PB	
		NO+NC		
	two wire system	NO	LMF22-3002LA	
		NC		
	AC 90~ 250 VAC	SCR Control- lable silicon	NO	
			NC	
			NO+NC	
Relay output				
Non-Flush	Detection distance		4mm	
	DC 6~ 36 VDC	NPN	NO	LMF22-3004NA
			NC	LMF22-3004NB
			NO+NC	
	PNP	NO	LMF22-3004PA	
		NC	LMF22-3004PB	
		NO+NC		
	two wire system	NO	LMF22-3004LA	
		NC		
	AC 90~ 250 VAC	SCR Control- lable silicon	NO	
			NC	
			NO+NC	
Relay output				
Control output	DC		200mA	
	SCR/ Relay		300mA	
Output voltage dropDC/AC		DC<3V、AC<10V		
Consumption current		DC<15mA、AC<10mA		
Standard detected object		15×15×1(A3 iron)		
Repeated precision		0.05		
DC/AC Response frequency		300Hz		
Working environment temperaturer		-25℃ ~+70℃		
Insulation resistance		≥50MΩ		
Shell material		ABS Resin		
Protection grade		IP67		
Alternative model at home and abroad				